checked by H

CETIFICATION

SDG No:

JC24978

Laboratory:

Accutest, New Jersey

Site:

BMSMC, Building 5 Area, PR

Matrix:

Groundwater

SUMMARY:

Groundwater samples (Table 1) were collected on the BMSMC facility – BMSMC, Building 5 Area, PR. The BMSMC facility is located in Humacao, PR. Samples were taken July 28-29, 2016 and were analyzed in Accutest Laboratory of Dayton, New Jersey for 1,4-Dioxane and Naphthalene. The results were reported under SDG No.: JC24978. Results were validated using the latest validation guidelines (July, 2015) of the EPA Hazardous Waste Support Section. The analyses performed are shown in Table 1. Individual data review worksheets are enclosed for each target analyte group. The data sample organic data samples summary form shows for analytes results that were qualified.

In summary the results are valid and can be used for decision taking purposes.

Table 1. Samples analyzed and analysis performed

SAMPLE ID	SAMPLE DESCRIPTION	MATRIX	ANALYSIS PERFORMED
JC24978-1	OSMS-2D	Groundwater	1,-4-dioxane and Naphthalene (SIM)
JC24978-1	OSMS-2D	Groundwater	1,-4-dioxane (SCAN)
JC24978-2	OSMW-2S	Groundwater	1,-4-dioxane and Naphthalene (SIM)
JC24978-2	OSMW-2S	Groundwater	1,-4-dioxane (SCAN)
JC24978-3	OSMW-2SD	Groundwater	1,-4-dioxane and Naphthalene (SIM)
JC24978-3	OSMW-2SD	Groundwater	1,-4-dioxane (SCAN)
JC24978-4	OSMW-1D	Groundwater	1,-4-dioxane and Naphthalene (SIM)
JC24978-4	OSMW-1D	Groundwater	1,-4-dioxane (SCAN)
JC24978-5	OSMW-1S	Groundwater	1,-4-dioxane and Naphthalene (SIM)
JC24978-5	OSMW-1S	Groundwater	1,-4-dioxane (SCAN)
JC24978-6	EB072816	AQ – Equipment Blank	1,-4-dioxane and Naphthalene (SIM)

Reviewer Name:

Rafael Infante

Chemist License 1888

Signature:

Date:

August 16, 2016

Report of Analysis

Page 1 of 1

Client Sample ID: OSMS-2D Lab Sample ID: JC24978-1

Matrix: Method:

Project:

AQ - Ground Water

SW846 8270D BY SIM SW846 3510C

BMSMC, Building 5 Area, PR

Date Sampled: 07/28/16

Date Received: 07/30/16

Percent Solids:

D . #1	File ID	DF	Analyzed	Ву	Prep Date	Prep Batch	Analytical Batch
Run #1	2M85994.D	1	07/31/16	KLS	07/30/16	OP95939A	E2M3807
Run #2	3M63395.D	1	08/02/16	SG	07/30/16	OP95939A	E3M3004

RL

MDL

Units

Q

Initial Volume Final Volume Run #1 910 ml $1.0 \, ml$ Run #2 910 ml $1.0 \, \mathrm{ml}$ Compound CAS No.

91-20-3 Naphthalene ND a 0.11 ug/l 0.032123-91-1 1,4-Dioxane 14.4 1.1 0.054 ug/I CAS No. Surrogate Recoveries Run#1 Run#2 Limits

Result

4165-60-0 Nitrobenzene-d5 71% 69% 24-125% 321-60-8 2-Fluorobiphenyl 69% 63% 19-127% 1718-51-0 Terphenyl-d14 77% 58% 10-119%

(a) Result is from Run# 2



ND = Not detected

MDL = Method Detection Limit

RL = Reporting Limit

E = Indicates value exceeds calibration range

J = Indicates an estimated value

B = Indicates analyte found in associated method blank

Report of Analysis

Page 1 of 1

Client Sample ID:	OSMW-2S
Lab Sample ID:	JC24978-2

Matrix: Method:

Run #1

AQ - Ground Water

Final Volume

1.0 ml

SW846 8270D BY SIM SW846 3510C

Date Sampled: 07/28/16 Date Received: 07/30/16

Percent Solids:

Project: BMSMC, Building 5 Area, PR

Initial Volume

950 ml

ī								
		File ID	DF	Analyzed	Ву	Prep Date	Prep Batch	Analytical Batch
	Run #1	2M85995.D	1	07/31/16	KLS	07/30/16	OP95939A	E2M3807
	Run #2	3M63396.D	1	08/02/16	SG	07/30/16	OP95939A	E3M3004

Run #2	950 ml	1.0 ml					
CAS No.	Compound		Result	RL	MDL	Units	Q
91-20-3 123-91-1	Naphthalene 1,4-Dioxane		ND ^a 16.4	0.11 1.1	0.031 0.051	ug/l ug/l	
CAS No.	Surrogate Reco	overies	Run# 1	Run# 2	Lim	its	
4165-60-0 321-60-8 1718-51-0	Nitrobenzene-d 2-Fluorobiphen Terphenyl-d14	_	77% 77% 66%	72% 65% 50%	19-1	25% 27% 19%	

(a) Result is from Run# 2



ND = Not detected

MDL = Method Detection Limit

RL = Reporting Limit

E = Indicates value exceeds calibration range

J = Indicates an estimated value

B = Indicates analyte found in associated method blank

Report of Analysis

Page 1 of 1

	Client Sample ID:	OSMW-2SD
Ì	Lab Sample ID:	JC24978-3
	T. P	4 (2) (2)

Matrix:

Run #1

AQ - Ground Water

Initial Volume Final Volume

1.0 ml

Method: Project:

930 ml

SW846 8270D BY SIM SW846 3510C

BMSMC, Building 5 Area, PR

Date Sampled: 07/28/16 Date Received: 07/30/16

Percent Solids:

	File ID	DF	Analyzed	Ву	Prep Date	Prep Batch	Analytical Batch
Run #1	2M85996.D	1	07/31/16	KLS	07/30/16	OP95939A	E2M3807
Run #2	3M63397.D	1	08/02/16	SG	07/30/16	OP95939A	E3M3004

Run #2	930 ml	1.0 ml					
CAS No.	Compound		Result	RL	MDL	Units	Q
91-20-3 123-91-1	Naphthalene 1,4-Dioxane		ND ^a 14.7	0.11	0.032 0.052	ug/l ug/l	
CAS No.	Surrogate R	Recoveries	Run#1	Run# 2	Lim	its	
4165-60-0 321-60-8 1718-51-0	Nitrobenzen 2-Fluorobipl Terphenyl-d	henyl	67% 64% 59%	59% 58% 47%	19-1	25% 27% 19%	

(a) Result is from Run# 2



ND = Not detected

MDL = Method Detection Limit

RL = Reporting Limit

E = Indicates value exceeds calibration range

J = Indicates an estimated value

B = Indicates analyte found in associated method blank

Report of Analysis

Page 1 of 1

Client Sample ID:	OSMW-1D
Lab Sample ID:	JC24978-4

Initial Volume

Terphenyl-d14

Matrix: Method:

Project:

AQ - Ground Water

SW846 8270D BY SIM SW846 3510C BMSMC, Building 5 Area, PR

Final Volume

Date Sampled: 07/29/16 Date Received: 07/30/16

Percent Solids: n/a

	File ID	DF	Analyzed	By	Prep Date	Prep Batch	Analytical Batch
Run #1	3M63398.D	1	08/02/16	SG	07/30/16	OP95939A	E3M3004
Run #2	2M86034.D	40	08/01/16	ΛN	07/30/16	OP95939A	E2M3808

91%

10-119%

Run #1 Run #2	930 ml 930 mi	1.0 ml 1.0 ml					
CAS No.	Compound		Result	RL	MDL	Units	Q
91-20-3 123-91-1	Naphthalene 1,4-Dioxane		ND 1290 ^a	0.11 43	0.032 2.1	ug/l ug/l	
CAS No.	Surrogate Rec	overies	Run# I	Run# 2	Lim	its	
4165-60-0 321-60-8	Nitrobenzene-d 2-Fluorobiphen		69% 68%	87% 95%		25% 27%	

65%

(a) Result is from Run# 2

1718-51-0



ND = Not detected

MDL = Method Detection Limit

RL = Reporting Limit

E = Indicates value exceeds calibration range

J = Indicates an estimated value

B = Indicates analyte found in associated method blank

Report of Analysis

Page 1 of 1

Client Sample ID:	OSMW-1S
Lab Sample ID:	JC24978-5

Initial Volume

Matrix:

AQ - Ground Water

Method: Project:

SW846 8270D BY SIM SW846 3510C

BMSMC, Building 5 Area, PR

Final Volume

Date Sampled: 07/29/16

Date Received: 07/30/16 Percent Solids:

Run #1	File ID 3M63399.D	DF 1	Analyzed 08/02/16	By SG	Prep Date 07/30/16	Prep Batch OP95939A	Analytical Batch E3M3004
Run #2	2M86035.D	20	08/01/16	ΛN	07/30/16	OP95939A	E2M3808

Run #1 Run #2	980 ml 980 ml	1.0 ml 1.0 ml					
CAS No.	Compound		Result	RL	MDL	Units	Q
91-20-3 123-91-1	Naphthalene 1,4-Dioxane		ND 1060 a	0.10 20	0.030 1.0	ug/l ug/j	
CAS No.	Surrogate Rec	coveries	Run# 1	Run# 2	Lim	its	
4165-60-0 321-60-8 1718-51-0	Nitrobenzene-d 2-Fluorobiphen Terphenyl-d14	-	56% 55% 64%	78% 85% 91%	19-1	25% 27% 19%	

(a) Result is from Run# 2



ND = Not detected

MDL = Method Detection Limit

RL = Reporting Limit

E = Indicates value exceeds calibration range

J = Indicates an estimated value

B = Indicates analyte found in associated method blank

Report of Analysis

Page 1 of 1

	Client Sample ID:	EB072816
	Lab Sample ID:	JC24978-6
ı	Mateix	AO Fouir

AQ - Equipment Blank SW846 8270D BY SIM SW846 3510C

Date Sampled: 07/28/16 Date Received: 07/30/16 Percent Solids: n/a

Units

ug/l ug/l Q

Method: Project:

BMSMC, Building 5 Area, PR

File ID DF Analyzed Ву Prep Date Prep Batch **Analytical Batch** Run #1 3P55423.D 1 08/02/16 AD 07/30/16 OP95939A E3P2534

Run #2

	Initial Volume	Final Volume
Run #1	950 ml	1.0 ml
Run #2		

CAS No.	Compound	Result	RL	MDL	U
91-20-3 123-91-1	Naphthalene 1,4-Dioxane	0.417 ND	0.11 0.11	0.031 0.051	uį uį
CAS No.	Surrogate Recoveries	Run#1	Run# 2	Lim	its
4165 CO O	Nitenhanzana dE	700/		24.1	250

4165-60-0	Nitrobenzene-d5	70%	24-125%
321-60-8	2-Fluorobiphenyl	59%	19-127%
1718-51-0	Terphenyl-d14	59%	10-119%



ND = Not detected

MDL = Method Detection Limit

RL = Reporting Limit

E = Indicates value exceeds calibration range

J = Indicates an estimated value

B = Indicates analyte found in associated method blank

	ACCLITEST	6	W		CHA	EN (OF (cus	TC	OD.	Y					AD9	1857	288	34	31			385 = 3		0.2	F <u> </u>
PHEN	NJ				223 TEL 732	324-0300	III, Diryte FAX 1 vaccidad	12-129-3	610 449/j.	490			35		-						1	200	+ +	下	N	49 78 J
	Client / Reporting Information				Project	t Inform	tation	100	913		-			1. 4		Raq	neth	d Ans	n) pale	(see	rest	COBE	sheet)		肥	Matrix Cod
	ary Minus														l i											100
5-4	rson Muthoffand & Associates Adress		SINSING Pho Sinus	en 2A Relogae	Assessmen	Rate of	Sec. 50	10.00	10 m	940	. 6	Anna a	2021	, 450	ğ											ON - Dreamy II ON - Growth V WW - Water
27861 Car	Woolchester Avenue, Suite 417						-								E270D			ŀ					- 9	- 1		SW Surface V
Punci	SOME Matter NY	dip.	Cay		PR	Compo	-								1 N					1					- 1	SL-Sh-dg SED-Sader
	Cornect	C-Mail	Humncao Project 8		- FR	Sireet	Salara and		_		-	_	_	_	Ě		-			1 :					- 1	CE CM
Ter	vy Taylor		921												훃					1	l				- 1	AR - Ar
Phone	# I-251-8400	Tax 8	Clare Purchase	Contor a		Cay							Ζþ		Mephthalane					1	ł	ш			- 1	SOL + Other 5 WP + Wipe
	rita Namatas	Ffront B	Province Manager			Allerda	in.		_		_				and N		12									FB-F-ett fine EB-Dqupmere D
N.	Rivera, R. Stuert, R. O'Relly, T. Te	bylor	Terry Taylor		Cologna		_	_		Numb	had od p		1 2-11-1		§		ē									TB-Trip Barr
	Field ID / Point of Collection		MALENTE	Date	D-m					100	ONO	2 2	0		1,4-0100										ı	LAB USE O
1	osww-25			7-28-16	1545	NR	GW	7	Ħ		Ħ	,	H		х			-	1	\vdash	\vdash			_	+	C-0 C32 C3
2	OSMW-25			7-22-16	17/8	NR	GW	2	Ħ		Н	2	1		X			-	-		-			-	-	1009
3	OSMW-25D			7-22-16	1730	NR	GW	2	Ħ	\top	┿	<u> </u>	H	Ħ	Х	\neg		_					\neg	-		-000
4	OSMW-ID	20.00		7-29-16	EPOI	۵۲	CaW	2	Ħ	\top	\rightarrow	1	H	Н	Х			_			-			-	\rightarrow	_
5	OSMW-IS		3	7-29-16	1150	JD	Gw	_	Ħ	\top	+ +	7	H	1-1	V	\dashv					-			-	+	
						Ť			⇈	_	Ħ	7	H	Ħ	~	\neg	-			-		\vdash		1	\pm	
	4,000				7				Ħ	\top	Н	+	H	Н										+	+	
						_			H	十	H	+	H٠	$^{+}$		-					-	-	-	-	+	
						-			Ħ	+	\Box	+	H	Н		-1	-		-				1	+	+	
			Sec. 143			\vdash			Ħ	$^{+}$	H	+	H	H			-		\vdash	-			-	+	-	
6	EB 072816			7-29-16	1/32	NR	EB	2	11	+	H	2	- -	11	X	\dashv	-		-	-			\rightarrow	-	+	
53	を 送出る は は できる は ない	45	485	SECTION .	A-2-14	45.4			H	S LE		5 3	9 6	[3]	1250	2.6	250	562	Mai	27.443	2000	-	5742	-		
21/2	Farment (1900 theorem dept)		40.0	CALL	1 100	() Pri , 10 g	0.0			4 27	tribur	2 E I	1 20	10-1	12	40 mg		735E	2.5	Come	north.	Spece	Page 1	town of the	-	-
]] SM. 16 Shminoon Days]] SM. 10 Shebbana Gays. (by Camboon :		phones de Spenie	oor Pility: 4 (Senior			Commence				_		ABP C	-												
	10 Day ACIDH						PULLT1 (9			ASP C		ny io	- F	-	-		_	_	_		7.1	-	
	T S Day HUEN 3 Day EMERGENCY	-			i	_	ILI Pintus				Ē	5 m	10 Par			_ [34 s		7
i	2 Day EMERGENCY	-				ш,		iaj non Carantaro	"A" lac	- Ren		04		_	man.					LABE	LVE	RIFIC	ATION	JE		
Energy (1 Stoy #3000400640CY Denny & Physik TJA disse produkto VAA (Labor				i			Comme	out "B"	- Non	ulto = 0	OC Bu	n-u-y			ľ									-	-
	CARRELL TOWARD		Sac	ple Custody my	at he decum	ented to	Open page	i i Pentur Libera sa		tangging O salbas	+ QC	-	ory = P olon,	in that i	دری محص	-	diam'r.		_		200-45	. 10 6.5	N 1981	75.00		
7	12820	7-29-	6 1700	Fee	1				-		B les	f	ز =					470	n 1	ارج:ه		0 Apr.	灵	52		
12		Oate Name									Der .		-			_	-1	770	//b_				_			-e
Police	detail by:	Bata Phase		3 Installed By:					4		-			п						[•					
									4	37 .	۳			0.		P	-			NO.			On yes	64	rater Tes	- 2.5°C-

JC24978: Chain of Custody Page 1 of 2

EXECUTIVE NARRATIVE

SDG No:

JC24978

Laboratory:

Accutest, New Jersey

Analysis:

SW846-8270D

Number of Samples:

6

Location:

BMSMC, Building 5 Area, PR

Humacao, PR

SUMMARY: Six (6) samples were analyzed for Naphthalene and 1,4-Dioxane following method SW846-8270D using the selective ion monitoring (SIM) technique; five of the samples were also analyzed for 1,4-Dioxane following method SW846-8270D in the scan mode. The sample results were assessed according to USEPA data validation guidance documents in the following order of precedence: EPA Hazardous Waste Support Section, SOP HW-35A, July 2015 –Revision 0. Semivolatile Data Validation. The QC criteria and data validation actions listed on the data review worksheets are from the primary guidance document, unless otherwise noted.

Results are valid and can be used for decision making purposes.

Critical issues:

None

Major: Minor:

None None

Critical findings:

None

Major findings:

None

Minor findings:

- 1. Naphthalene detected in the equipment blank at a concentration above reporting limit.
- No action taken, Naphthalene not detected in the sample batch.
- 2. MS/MSD % recovery RPD for 1,4-Dioxane outside the laboratory control limits, but within generally acceptable control limits. No action taken, professional judgment.

COMMENTS:

Results are valid and can be used for decision making purposes.

Reviewers Name:

Rafael Infante

Chemist License 1888

Signature:

Date:

August 16, 2016

SAMPLE ORGANIC DATA SAMPLE SUMMARY

Sample ID: JC24978-1

Sample location: BMSMC, Building 5 Area, PR

Sampling date: 7/28/2016 Matrix: Groundwater

METHOD: 8270D (SIM)

Analyte Name Result

Units Dilution Factor Lab Flag Validation Reportable Naphthalene 0.11 ug/l U

1,4-Dioxane

METHOD: 8270D (SCAN)

Analyte Name Result Units Dilution Factor Lab Flag Validation Reportable

1,4-Dioxane

14.4 ug/l 1 U Yes

Sample ID: JC24978-2

Sample location: BMSMC, Building 5 Area, PR

Sampling date: 7/28/2016 Matrix: Groundwater

METHOD: 8270D (SIM)

Analyte Name Result Units Dilution Factor Lab Flag Validation Reportable

Naphthalene 0.11 ug/l U Yes 1,4-Dioxane

METHOD: 8270D (SCAN)

Analyte Name Units Dilution Factor Lab Flag Validation Reportable Result

1,4-Dioxane 16.4 1 ug/l U Yes

Sample ID: JC24978-3

Sample location: BMSMC, Building 5 Area, PR

Sampling date: 7/28/2016 Matrix: Groundwater

METHOD: 8270D (SIM)

Analyte Name Result Units Dilution Factor Lab Flag Validation Reportable

Naphthalene 0.11 ug/l U Yes 1,4-Dioxane

METHOD: 8270D (Scan)

Analyte Name Result Units Dilution Factor Lab Flag Validation Reportable

1,4-Dioxane 14.7 ug/l 1 Yes Sample ID: JC24978-4

Sample location: BMS-ICM, Humacao, PR

Sampling date: 7/29/2016 Matrix: Groundwater

METHOD: 8270D (SIM)

Analyte Name Result Units Dilution Factor Lab Flag Validation Reportable
Naphthalene 0.11 ug/l 1 - U Yes
1,4-Dioxane - - - - - - -

METHOD: 8270D (Scan)

Analyte Name Result Units Dilution Factor Lab Flag Validation Reportable 1,4-Dioxane 1290 ug/l 40 - Yes

Sample ID: JC24978-5

Sample location: BMS-ICM, Humacao, PR

Sampling date: 1/29/2016 Matrix: Groundwater

METHOD: 8270D (SIM)

Analyte Name Result Units Dilution Factor Lab Flag Validation Reportable

Naphthalene 0.10 ug/l 1 - U Yes

1,4-Dioxane - - - - - -

METHOD: 8270D (Scan)

Analyte Name Result Units Dilution Factor Lab Flag Validation Reportable 1,4-Dioxane 1060 ug/l 20 - - Yes

Sample ID: JC24978-6

Sample location: BMS-ICM, Humacao, PR

Sampling date: 7/28/2016

Matrix: AQ - Equipment Blank

METHOD: 8270D (SIM)

Analyte Name Result Units Dilution Factor Lab Flag Validation Reportable

Naphthalene 0.417 ug/l 1 - U Yes

1,4-Dioxane 0.11 ug/l 1 - U Yes

	Project Number: _JC24978 Date: July_28-July_29,_2016 Shipping Date:July_29,_2016 EPA Region:2
REVIEW OF SEMIVOLATILE OF	RGANIC PACKAGE
The following guidelines for evaluating volatile organ validation actions. This document will assist the remarks more informed decision and in better serving results were assessed according to USEPA data following order of precedence: EPA Hazardous W. 2015 –Revision 0. Semivolatile Data Validation. The QC on the data review worksheets are from the primare noted.	viewer in using professional judgment to the needs of the data users. The sample validation guidance documents in the aste Support Section, SOP HW-35A, July criteria and data validation actions listed
The hardcopied (laboratory name) _Accutest reviewed and the quality control and performance data included:	
Lab. Project/SDG No.:JC24978 No. of Samples:6_SIM/5_SCAN	
Trip blank No.:	
X GC/MS TuningX Internal Standard PerformanceX Blanks	X Laboratory Control SpikesX Field DuplicatesX CalibrationsX Compound IdentificationsX Compound QuantitationX Quantitation Limits
_Overall Comments:_Naphthalene_and_1,4-Dioxane_anal _Samples_JC24978-1_to_JC24978-5_also_analyzed_by_t	yzed_by_method_SW846-8270D_(SIM); the_scan_method
Definition of Qualifiers:	
J- Estimated results U- Compound not detected R- Rejected data UJ- Estimated nondetect Reviewer:	

DATA COMPLETENESS

MISSING INFORMATION	DATE LAB. CONTACTED	DATE RECEIVED
4		
		4
333		

All criteria were met _X	
Criteria were not met	
and/or see below	

HOLDING TIMES

The objective of this parameter is to ascertain the validity of the results based on the holding time of the sample from time of collection to the time of analysis.

Complete table for all samples and note the analysis and/or preservation not within criteria

SAMPLE ID	DATE SAMPLED	DATE EXTRACTED/ANALYZED	pН	ACTION				
All samples extracted and analyzed within method recommended holding time. Samples propreserved except in the cases described in this document.								
Cooler temperate	(Onite view A	2001 400						

Cooler temperature (Criteria: 4 ± 2 °C): ______4°C_____

<u>Actions</u>

Results will be qualified based on the criteria of the following Table:

Table 1. Holding Time Actions for Semivolatile Analyses

		ing time Actions for Semiv		tion			
Matrix	Preserved	Criteria	Detected Associated Compounds	Non-Detected Associated Compounds			
	No	≤7 days (for extraction) ≤40 days (for analysis)	Use profession	onal judgment			
	No	> 7 days (for extraction) > 40 days (for analysis)	j	Use professional judgment			
Aqueous	Yes	≤ 7 days (for extraction) ≤ 40 days (for analysis)	No qualification				
	Yes	> 7 days (for extraction) > 40 days (for analysis)	1	נט			
	Yes/No	Grossly Exceeded	J	UJ or R			
	No	≤ 14 days (for extraction) ≤ 40 days (for analysis)	Use profession	onal judgment			
Ni A	No	> 14 days (for extraction) > 40 days (for analysis)	J	Use professional judgment			
Non-Aqueous	Yes	≤ 14 days (for extraction) ≤ 40 days (for analysis)	No qua	lification			
	Yes	> 14 days (for extraction) > 40 days (for analysis)	J	บม			
	Yes/No	Grossly Exceeded	j	UJ or R			

List	the	samples	affected:
	The requirement to analyze the analysis of PAHs/pentachloroph	•	-
Notes:	All mass spectrometer condition analysis. Background subtract unacceptable No data should be qualified base	tion actions resulting i	
Notes:	These requirements do not ap Monitoring (SIM) technique.	oly when samples are and	alyzed by the Selected Ion
If no, use profe or rejected.	ssional judgment to determine wh	ether the associated data s	hould be accepted, qualified
_X DFTPF	tuning was performed for every 1	2 hours of sample analysis	
_X The DF	TPP performance results were re	viewed and found to be witl	hin the specified criteria.
The assessmentuning QC limits	nt of the tuning results is to determs	nine if the sample instrumen	ntation is within the standard
GC/MS TUNIN	G		
			Criteria were not met see below

Actions:

- 1. If sample are analyzed without a preceding valid instrument performance check or are analyzed 12 hours after the Instrument Performance Check, qualify all data in those samples as unusable (R).
- 2. If ion abundance criteria are not met, use professional judgment to determine to what extent the data may be utilized.
- 3. State in the Data Review Narrative, decisions to use analytical data associated with DFTPP instrument performance checks not meeting the contract requirements.
- 4. Use professional judgment to determine if associated data should be qualified based on the spectrum of the mass calibration compounds.

All criteria were metX
Criteria were not met
and/or see below

INITIAL CALIBRATION VERIFICATION

Compliance requirements for satisfactory instrument calibration are established to ensure that the instrument is capable of producing and maintaining acceptable quantitative data.

Instrument ID numbers:GCMS3P	Date of initial calibration:07/20-21/16_(SCAN) Instrument ID numbers:GCMS2M
Matrix/Level:Aqueous/low	Matrix/Level:Aqueous/low
Date of initial calibration:_07/14/16_(SCAN)_ Instrument ID numbers:GCMS3M Matrix/Level:Aqueous/low	·
DATE LAB FILE CRITERIA OUT	COMPOUND SAMPLES

DATE		FILE	CRITERIA OUT	COMPOUND	SAMPLES		
	ID#		RFs, %RSD, %D, r		AFFECTED		
1 11 1	1 1 14	1 401	4* *** 4*				
Initial a	Initial and initial calibration verification meets the method and guidance validation document						
performance criteria.							

Note:

Actions:

Qualify the initial calibration analytes listed in Table 2 using the following criteria:

Table 3. Initial Calibration Actions for Semivolatile Analysis

Criteria	Action		
Спіств	Detect	Non-detect	
Initial Calibration not performed at specified frequency and sequence	Use professional judgment R	Use professional judgment R	
Initial Calibration not performed at the specified concentrations	J	U	
RRF < Minimum RRF in Table 2 for target analyte	Use professional judgment J+ or R	R	
RRF ≥ Minimum RRF in Table 2 for target analyte	No qualification	No qualification	
%RSD > Maximum %RSD in Table 2 for target analyte	J	Use professional judgment	
%RSD ≤ Maximum %RSD in Table 2 for target analyte	No qualification	No qualification	

Initial Calibration

Table 2. RRF, %RSD, and %D Acceptance Criteria in Initial Calibration and CCV for Semivolatile Analysis

Analyte	Minimum RRF	Maximum %RSD	Opening Maximum %D ^t	Opening Maximum %D ¹
1,4-Dioxane	0.010	40.0	± 40.0	±50.0
Benzaldehyde	0,100	40.0	± 40.0	± 50.0
Phenoi	0.080	20.0	± 20.0	±25.0
Bis(2-chloroethyl)ether	0.100	20.0	±20.0	±25.0
2-Chlorophenol	0.200	20.0	± 20.0	±25.0
2-Methylphenol	0.010	20.0	±20.0	±25.0
3-Methylphenol	0.010	20.0	± 20.0	±25.0
2,2'-Oxybis-(1-chloropropane)	0.010	20.0	±25.0	±50.0
Acetophenone	0.060	20.0	± 20.0	±25.0
4-Methylphenol	0.010	20.0	±20.0	±25.0
N-Nitroso-di-n-propylamine	0.080	20.0	±25.0	±25.0
Hexachloroethane	0.100	20.0	± 20.0	± 25.0
Nitrobenzene	0.090	20.0	± 20.0	±25.0
Isophorone	0.100	20.0	±20.0	±25.0
2-Nitrophenol	0.060	20.0	±20.0	±25.0
2,4-Dimethylphenol	0.050	20.0	±25.0	±50.0
Bis(2-chloroethoxy)methane	0.080	20.0	±20.0	± 25.0
2,4-Dichlorophenol	0.060	20.0	± 20.0	±25.0
Naphthalene	0.200	20.0	± 20.0	± 25.0
4-Chloroaniline	0.010	40.0	± 40.0	± 50.0
lexachlorobutadiene	0.040	20.0	± 20.0	± 25.0
Caprolactam	0.010	40.0	±30.0	± 50.0
4-Chloro-3-methylphenol	0.040	20.0	± 20.0	± 25.0
2-Methylnaphthalene	0.100	20.0	± 20.0	±25.0
lexachlorocyclopentadiene	0.010	40.0	± 40.0	± 50.0
2,4,6-Trichlorophenol	0.090	20.0	± 20.0	±25.0
2,4,5-Trichlorophenol	0.100	20.0	±20.0	±25.0
I, I'-Biphenyl	0.200	20.0	± 20.0	± 25.0

Analyte	Minimum RRF	Maximum %RSD	Opening Maximum %D ^t	Opening Maximum %D ¹
2-Chloronaphthalene	0.300	20.0	±20.0	±25.0
2-Nitroaniline	0.060	20.0	±25.0	±25.0
Dimethylphthalate	0.300	20.0	±25.0	±25.0
2,6-Dinitrotoluene	0.080	20.0	±20.0	±25.0
Acenaphthylene	0.400	20.0	±20.0	±25.0
3-Nitroaniline	0.010	20.0	±25.0	±50.0
Acenaphthene	0.200	20.0	± 20.0	±25.0
2,4-Dinitrophenol	0.010	40.0	± 50.0	± 50.0
4-Nitrophenol	0.010	40.0	±40.0	±50.0
Dibenzofuran	0.300	20.0	±20.0	±25.0
2,4-Dinitrotoluene	0.070	20.0	±20.0	±25.0
Diethylphthalate	0.300	20.0	± 20.0	±25.0
1,2,4,5-Tetrachlorobenzene	0.100	20.0	± 20.0	±25.0
4-Chlorophenyl-phenylether	0.100	20.0	± 20.0	±25.0
Fluorene	0.200	20.0	±20.0	±25.0
4-Nitroaniline	0.010	40.0	±40.0	±50.0
4,6-Dinitro-2-methylphenol	0.010	40.0	±30.0	± 50.0
4-Bromophenyl-phenyl ether	0.070	20.0	±20.0	±25.0
N-Nitrosodiphenylamine	0.100	20.0	±20.0	±25.0
Hexachlorobenzene	0.050	20.0	±20.0	±25.0
Atrazine	0.010	40.0	±25.0	±50.0
Pentachlorophenol	0.010	40.0	±40.0	±50.0
Phenanthrene	0.200	20.0	±20.0	±25.0
Anthracene	0.200	20.0	±20.0	±25.0
Carbazole	0.050	20.0	±20.0	±25.0
Di-n-buty/lphthalate	0.500	20.0	±20.0	±25.0
Fluoranthene	0.100	20.0	± 20.0	±25.0
Pyrene	0.400	20.0	±25.0	±50.0
Butylbenzylphthalate	0.100	20.0	±25.0	±50.0

Analyte	Minimum RRF	Maximum %RSD	Opening Maximum %D¹	Opening Maximum %D ¹
3,3'-Dichlorobenzidine	0.010	40.0	±40.0	± 50.0
Benzo(a)anthracene	0.300	20.0	±20.0	±25.0
Chrysene	0.200	20.0	± 20.0	± 50.0
Bis(2-ethylhexyl) phthalate	0.200	20.0	±25.0	± 50.0
Di-n-octylphthalate	0.010	40.0	± 40.0	± 50.0
Benzo(b)fluoranthene	0.010	20.0	±25.0	± 50.0
Benzo(k)fluoranthene	0.010	20.0	±25.0	± 50.0
Benzo(a)pyrene	0.010	20.0	± 20.0	± 50.0
Indeno(1,2,3-cd)pyrene	0.010	20.0	±25.0	± 50.0
Dibenzo(a,h)anthracene	0.010	20.0	±25.0	± 50.0
Benzo(g,h,i)perylene	0.010	20.0	±30.0	± 50.0
2,3,4,6-Tetrachlorophenol	0.040	20.0	± 20.0	± 50.0
Naphthalene	0.600	20.0	±25.0	±25.0
2-Methylnaphthalene	0.300	20.0	± 20.0	± 25.0
Acenaphthylene	0.900	20.0	± 20.0	± 25.0
Acenaphthene	0.500	20.0	± 20.0	± 25.0
Fluorene	0.700	20,0	±25.0	± 50.0
Phenanthrene	0.300	20.0	±25.0	± 50.0
Anthracene	0.400	20.0	±25.0	± 50.0
Fluoranthene	0.400	20.0	±25.0	± 50.0
Pyrene	0.500	20.0	± 30.0	± 50.0
Benzo(a)anthracene	0.400	20.0	±25.0	± 50.0
Chyrsene	0.400	20.0	±25.0	± 50.0
Benzo(b)fluoranthene	0.100	20.0	±30.0	± 50.0
Benzo(k)fluoranthene	0.100	20.0	± 30.0	± 50.0
Benzo(a)pyrene	0.100	20.0	±25.0	± 50.0
Indeno(1,2,3-cd)pyrene	0.100	20.0	± 40.0	± 50.0
Dibenzo(a,h)anthracene	0.010	25.0	± 40.0	± 50.0
Benzo(g,h,i)perylene	0.020	25.0	±40.0	± 50.0

Pentachlorophenol	0.010	40.0	± 50.0	± 50.0	
Deuterated Monitoring Compounds					

Analyte	Minimum RRF	Maximum %RSD	Opening Maximum %D ^t	Closing Maximum %D
1,4-Dioxane-d ₈	0.010	20.0	±25.0	± 50.0
Phenol-ds	0.010	20.0	±25.0	±25.0
Bis-(2-chloroethyl)ether-d ₈	0.100	20.0	± 20.0	± 25.0
2-Chlorophenol-d ₄	0,200	20.0	± 20.0	± 25.0
4-Methylphenol-d ₈	0.010	20.0	±20.0	±25.0
4-Chloroaniline-d ₄	0.010	40.0	±40.0	± 50.0
Nitrobenzene-d₅	0.050	20.0	±20.0	±25.0
2-Nitrophenol-d ₄	0.050	20.0	±20.0	± 25.0
2,4-Dichlorophenol-d;	0.060	20.0	±20.0	± 25.0
Dimethylphthalate-d ₆	0.300	20.0	± 20.0	± 25.0
Acenaphthylene-d ₈	0.400	20.0	±20.0	± 25.0
4-Nitrophenol-d ₄	0.010	40.0	± 40.0	± 50.0
Fluorene-dia	0.100	20.0	± 20.0	± 25.0
4,6-Dinitro-2-methylphenol-d2	0.010	40.0	±30.0	±50.0
Anthracene-d ₁₀	0.300	20.0	±20.0	± 25.0
Pyrene-d ₁₀	0.300	20.0	±25.0	± 50.0
Benzo(a)pyrene-d ₁₂	0.010	20.0	± 20.0	± 50.0
Fluoranthene-d ₁₀ (SIM)	0.400	20.0	±25.0	± 50.0
2-Methylnaphthalene-d ₁₀ (SIM)	0.300	20.0	± 20.0	± 25.0

If a closing CCV is acting as an opening CCV, all target analytes must meet the requirements for an opening CCV.

Note: If analysis by SIM technique is requested for PAH/pentachlorophenols, calibration standards analyzed at 0.10, 0.20, 0.40, 0.80, and 1.0 ng/uL for each target compound of interest and the associated DMCs. Pentachlorophenol will require only a four point initial calibration at 0.20, 0.40, 0.80, and 1.0 ng/uL.

				All criteria were metX Criteria were not met and/or see below
CONTINU	JING CALIB	RATION VERIFICATION	N	
			nstrument calibration are aining acceptable quantita	established to ensure that the tive data.
Date of ini Date of co Date of clo Instrumen	tial calibrati Intinuing cal Ising CCV:_ t ID number	on verification (ICV): libration verification (CC\ rs:(06/16_(SIM) 07/06/16 V):_08/02/16;_08/09/16_ GCMS3P ueous/low	07/14/16_(SIM) 07/14/16 08/02/16 GCMS3M Aqueous/low
Date of ini Date of ini Date of co	tial calibrati tial calibrati Intinuing cal	on:07/2	20-21/16_(Scan) 07/20-21/16	_
Instrumen	t ID number	rs:(GCM2M	
Matrix/Lev	/el:	Aq	ueous/low	
DATE	LAB FIL ID#	E CRITERIA OUT RFs, %RSD, %D, r	1	SAMPLES AFFECTED

Note: Initial and continuing calibration verifications meet the method and guidance document required performance criteria. No closing calibration verification included in data package. No action taken, professional judgment.

Actions:

Notes: Verify that the CCV is run at the required frequency (an opening and closing CCV must be run within 12-hour period).

All DMCs must meet the RRF values given in Table 2. No qualification of the data is necessary on DMCs RRF and %RSD/%D alone. Use professional judgment to evaluate DMCs and %RSD/%D data in conjunction with DMCs recoveries to determine the need for qualification of the data.

Qualify the initial calibration analytes listed in Table 2 using the following criteria in the CCVs:

Table 4. CCV Actions for Semivolatile Analysis

Criteria for Opening CCV	Criteria for Closing CCV	Action		
Criteria for Opening CC4	Criteria for Clusting CCV	Detect	Non-detect	
CCV not performed at required frequency and sequence	CCV not performed at required frequency	Use professional judgment R	Use professional judgment R	
CCV not performed at specified concentration	CCV not performed at specified concentration	Use professional judgment	Use professional judgment	
RRF < Minimum RRF in Table 2 for target analyte	RRF < Minimum RRF in Table 2 for target analyte	Use professional judgment J or R	R	
RRF ≥ Minimum RRF in Table 2 for target analyte	RRF ≥ Minimum RRF in Table 2 for target analyte	No qualification	No qualification	
%D outside the Opening Maximum %D limits in Table 2 for target analyte	%D outside the Closing Maximum %D limits in Table 2 for target analyte	1	ÚJ	
%D within the inclusive Opening Maximum %D limits in Table 2 for target analyte	%D within the inclusive Closing Maximum %D limits in Table 2 for target analyte	No qualification	No qualification	

All criteria were met
Criteria were not met
and/or see belowX

BLANK ANALYSIS RESULTS (Sections 1 & 2)

The assessment of the blank analysis results is to determine the existence and magnitude of contamination problems. The criteria for evaluation of blanks apply only to blanks associated with the samples, including trip, equipment, and laboratory blanks. If problems with any blanks exist, all data associated with the case must be carefully evaluated to determine whether or not there is an inherent variability in the data for the case, or if the problem is an isolated occurrence not affecting other data.

List the contamination in the blanks below. High and low levels blanks must be treated separately.

Notes: The concentration of non-target compounds in all blanks must be less than or equal to 10 ug/L.

The concentration of target compounds in all blanks must be less than its CRQL listed in the method.

Samples taken from a drinking water tap do not have and associated field blank.

Laboratory blanks

DATE ANALYZED	LAB ID	LEVEL/ Matrix	COMPOUND	CONCENTRATION UNITS
_No_target_ana	alytes_detected_	_in_method_bla	nks	
Field/ <u>Equipmen</u>	<u>t</u> /Trip blank			
DATE ANALYZED	LAB ID	LEVEL/ MATRIX	COMPOUND	CONCENTRATION UNITS
				the_cases_described_in_this
_08/02/16	JC24978-6	_Aqueous/low_	Naphthaiene	0.417_ug/l
		000 HF 1950		- 19 <u>48,400 - 48</u> - 13
		- 2		

Note: No action taken, naphthalene not detected in sample batch.

All criteria were metX
Criteria were not met
and/or see below

BLANK ANALYSIS RESULTS (Section 3)

Blank Actions

Qualify samples based on the criteria summarized in Table 5:

Table 5. Blank and TCLP/SPLP LEB Actions for Semivolatile Analysis

Blank Type	Blank Result	Sample Result	Action
	Detect	Non-detect	No qualification
	< CRQL	< CRQL	Report at CRQL and qualify as non-detect (U)
		≥ CRQL	Use professional judgment
		< CRQL	Report at CRQL and qualify as non-detect (U)
Method,		≥ CRQL but < Blank Result	Report at sample results and qualify as non-detect (U) or as unusable (R)
TCLP/SPLP LEB, Field		≥ CRQL and ≥ Blank Result	Use professional judgment
	Grossly high	Detect	Report at sample results and qualify as unusable (R)
	TIC > 5.0 ug/L (water) or 0.0050 mg/L (TCLP leachate) or TIC > 170 ug/Kg (soil)	Detect	Use professional judgment

List samples qualified

CONTAMINATION SOURCE/LEVEL	COMPOUND	CONC/UNITS	AL/UNITS	SQL	AFFECTED SAMPLES
					-
			l		

All criteria were metX
Criteria were not met
and/or see below

SURROGATE SPIKE RECOVERIES - DEUTERATED MONITORING COMPOUNDS (DMCs)

Laboratory performance of individual samples is established by evaluation of surrogate spike recoveries – deuterated monitoring compounds. All samples are spiked with surrogate compounds prior to sample analysis. The accuracy of the analysis is measured by the surrogate percent recovery. Since the effects of the sample matrix are frequently outside the control of the laboratory and may present relatively unique problems, the validation of data is frequently subjective and demands analytical experience and professional judgment.

Notes: Recoveries for DMCs in samples and blanks must be within the limits specified in Table 6.

The recovery limits for any of the compounds listed in Table 6 may be expanded at any time during the period of performance if USEPA determines that the limits are too restrictive.

If a DMC is not added in the samples and blanks or the concentrations of DMCs in the samples and blank not the specified, use professional judgment in qualifying the data.

Table 7. DMC Actions for Semivolatile Analysis

Criteria	Action		
Criteria	Detect	Non-detect	
%R < 10% (excluding DMCs with 10% as a lower acceptance limit)	J-	R	
10% ≤ %R (excluding DMCs with 10% as a lower acceptance limit) < Lower Acceptance Limit	J-	UJ	
Lower Acceptance limit $\leq \%R \leq Upper Acceptance Limit$	No qualification	No qualification	
%R > Upper Acceptance Limit	J+	No qualification	

SAMPLE ID	SURROGATE COMPOUND	ACTION
	uired_criteriaNondeuterated_surrogates_adde overy_limits	

Table 8. Semivolatile DMCs and the Associated Target Analytes

1,4-Dioxane-da (DMC-1)	Phenol-d ₅ (DMC-2)	Bis(2-Chloroethyl) ether-d ₈ (DMC-3)
1,4-Dioxane	Benzaldehyde	Bis(2-chloroethyl)ether
	Phenol	2,2'-Oxybis(1-chloropropane)
		Bis(2-chloroethoxy)methane
2-Chlorophenol-d ₄ (DMC-4)	4-Methylphenol-da (DMC-5)	4-Chloroaniline-d ₄ (DMC-6)
2-Chlorophenol	2-Methylphenol	4-Chloroaniline
	3-Methylphenol	Hexachlorocyclopentadiene
	4-Methylphenol	Dichlorobenzidine
	2,4-Dimethylphenol	
Nitrobenzene-d ₅ (DMC-7)	2-Nitrophenol-d ₄ (DMC-8)	2,4-Dichlorophenol-d3(DMC-9)
Acetophenone	Isophorone	2,4-Dichlorophenol
N-Nitroso-di-n-propylamine	2-Nitrophenol	Hexachlorobutadiene
Hexachloroethane		Hexachlorocyclopentadiene
Nitrobenzene		4-Chloro-3-methylphenol
2,6-Dinitrotoluene		2,4,6-Trichlorophenol
2,4-Dinitrotoluene		2,4,5-Trichlorophenol
N-Nitrosodiphenylamine		1,2,4,5-Tetrachlorobenzene
		*Pentachlorophenol
		2,3,4,6-Tetrachlorophenol
Dimethylphthalate-d ₆ (DMC-10)	Acenaphthylene-da (DMC-11)	4-Nitrophenol-d ₄ (DMC-12)
Caprolactam	*Naphthalene	2-Nitroaniline
1,1'-Biphenyl	*2-Methylnaphthalene	3-Nitroanitine
Dimethylphthalate	2-Chloronaphthalene	2,4-Dinitrophenol
Diethylphthalate	*Acenaphthylene	4-Nitrophenol
Di-n-butylphthalate	*Acenaphthene	4-Nitroaniline
Butylbenzylphthalate		
Bis(2-ethylhexyl) phthalate		
Di-n-octylphthalate		

Fluorene-d ₁₀ (DMC-13)	4,6-Dinitro-2-methylphenol-d ₂ (DMC-14)	Anthracene-d ₁₀ (DMC-15)
Dibenzofuran *Fluorene 4-Chlorophenyl-phenylether 4-Bromophenyl-phenylether Carbazole	4,6-Dinitro-2-methylphenol	Hexachlorobenzene Atrazine *Phenanthrene *Anthracene
Pyrene-d ₁₀ (DMC-16)	Benzo(a)pyrene-d ₁₂ (DMC-17)	
*Fluoranthene	3,3'-Dichlorobenzidine	
*Pyrene	*Benzo(b)fluoranthene	
*Benzo(a)anthracene	*Benzo(k)fluoranthene	
*Chrysene	*Benzo(a)pyrene	
	*Indeno(1,2,3-cd)pyrene	
	*Dibenzo(a,h)anthracene	
	*Benzo(g,h,i)perylene	

^{*}Included in optional Target Analyte List (TAL) of PAHs and PCP only.

Table 9. Semivolatile SIM DMCs and the Associated Target Analytes

Fluoranthene-d10 (DMC-1)	2-Methylnaphthalene-d10 (DMC-2)
Fluoranthene	Naphthalene
Pyrene	2-Methylnaphthalene
Benzo(a)anthracene	Acenaphthylene
Chrysene	Acenaphthene
Benzo(b)fluoranthene	Fluorene
Benzo(k)fluoranthene	Pentachlorophenol
Benzo(a)pyrene	Phenanthrene
Indeno(1,2,3-cd)pyrene	Anthracene
Dibenzo(a,h)anthracene	
Benzo(g,h,i)perylene	

All criteria were met	
Criteria were not met	
and/or see below	_X

VII. A MATRIX SPIKE/MATRIX SPIKE DUPLICATE (MS/MSD)

This data is generated to determine long term precision and accuracy in the analytical method for various matrices. This data alone cannot be used to evaluate the precision and accuracy of individual samples. If any % R in the MS or MSD falls outside the designated range, the reviewer should determine if there are matrix effects, i.e. LCS data are within the QC limits but MS/MSD data are outside QC limit.

1. MS/MSD Recoveries and Precision Criteria

The laboratory should use one MS and a duplicate analysis of an unspiked field sample if target analytes are expected in the sample. If target analytes are not expected, MS/MSD should be analyzed.

NOTES:

Data for MS and MSDs will not be present unless requested by the Region. Notify the Contract Laboratory COR if a field or trip blank was used for the MS and MSD.

For a Matrix Spike that does not meet criteria, apply the action to only the field sample used to prepare the Matrix Spike sample. If it is clearly stated in the data validation materials that the samples were taken through incremental sampling or some other method guaranteeing the homogeneity of the sample group, then the entire sample group may be qualified.

List the %Rs, RPD of the compounds which do not meet the criteria.

Sample ID:	JC24	978-2_					Matrix	Level:_	Gro	undwater
The QC reports				_	•				6 8270D	BY SIM
	JC249	78-2	Spike	MS	MS	Spike	MSD	MSD		Limits
Compound	ug/l	Q	ug/l	ug/l	%	ug/l	ug/l	%	RPD	Rec/RPD
Naphthalene	ND		1.09	0.826	76	1.1	0.824	75	0	23-140/36
1,4-Dioxane	ND		1.09	0.600	55	1.1	0.437	40	31*a	20-160/30

(a) Analytical precision exceeds in-house control limits.

Note: MS/MSD % recoveries and RPD within laboratory control limits except in the cases described in this document. RPD for 1,4-dioxane outside laboratory control limits. No action taken, professional judgment.

- * QC limits are laboratory in-house performance criteria, LL = lower limit, UL = upper limit.
- * If QC limits are not available, use limits of 70 130 %.

Actions:

QUALITY	%R < LL	%R > UL
Positive results	J	J
Nondetects results	R	Accept

MS/MSD criteria apply only to the unspiked sample, its dilutions, and the associated MS/MSD samples:

If the % R for the affected compounds were < LL (or 70 %), qualify positive results (J) and nondetects (UJ).

If the % R for the affected compounds were > UL (or 130 %), only qualify positive results (J). If 25 % or more of all MS/MSD %R were < LL (or 70 %) or if two or more MS/MSD %Rs were < 10%, qualify all positive results (J) and reject nondetects (R).

A separate worksheet should be used for each MS/MSD pair.

All criteria were met _X
Criteria were not met
and/or see below

INTERNAL STANDARD PERFORMANCE

The assessment of the internal standard (IS) parameter is used to assist the data reviewer in determining the condition of the analytical instrumentation.

List the internal standard area of samples which do not meet the criteria.

DATE SAMPLE ID IS OUT IS AREA ACCEPTABLE ACTION RANGE

Internal area meets the required criteria of batch samples corresponding to this data package.

Action:

- If an internal standard area count for a sample or blank is greater than 213.0% of the area for the associated standard (opening CCV or mid-point standard from initial calibration) (see Table 10 below):
 - a. Qualify detects for compounds quantitated using that internal standard as estimated low (J-).
 - Do not qualify non-detected associated compounds.
- 2. If an internal standard area count for a sample or blank is less than 20.0% of the area for the associated standard (opening CCV or mid-point standard from initial calibration):
 - a. Qualify detects for compounds quantitated using that internal standard as estimated high (J+).
 - b. Qualify non-detected associated compounds as unusable (R).
- 3. If an internal standard area count for a sample or blank is greater than or equal to 50.0%, and less than or equal to 213% of the area for the associated standard opening CCV or mid-point standard from initial calibration, no qualification of the data is necessary.
- 4. If an internal standard RT varies by more than 10.0 seconds: Examine the chromatographic profile for that sample to determine if any false positives or negatives exist. For shifts of a large magnitude, the reviewer may consider partial or total rejection of the data for that sample fraction. Detects should not need to be qualified as unusable (R) if the mass spectral criteria are met.
- 5. If an internal standard RT varies by less than or equal to 10.0 seconds, no qualification of the data is necessary.

Note: Inform the Contract Laboratory Program Project Officer (CLP PO) if the internal standard performance criteria are grossly exceeded. Note in the Data Review Narrative potential effects on the data resulting from unacceptable internal standard performance.

State in the Data Review Narrative if the required internal standard compounds are not added to a sample or blank or if the required internal standard compound is not analyzed at the specified concentration.

Actions:

Table 10. Internal Standard Actions for Semivolatile Analysis

Criteria	Action		
Criteria	Detect	Non-detect	
Area response < 20% of the opening CCV or mid-point standard CS3 from ICAL	J+	R	
20% ≤ Area response < 50% of the opening CCV or mid-point standard CS3 from ICAL	J+	UJ	
50% ≤ Area response ≤ 200% of the opening CCV or mid-point standard CS3 from ICAL	No qualification	No qualification	
Area response > 200% of the opening CCV or mid-point standard CS3 from ICAL	J-	No qualification	
RT shift between sample/blank and opening CCV or mid-point standard CS3 from ICAL > 10.0 seconds	R	R	
RT shift between sample/blank and opening CCV or mid-point standard CS3 from ICAL < 10.0 seconds	No qualification	No qualification	

		All criteria were metX Criteria were not met and/or see below
TARGET COM	POUND IDENTIFICATION	
Criteria:		
		ounds within ±0.06 RRT units of the standard V) or mid-point standard from the initial Yes? or No?
List compound	Is not meeting the criteria described above:	
Sample ID	Compounds	Actions
spectrum from	a the associated calibration standard (oper ust match according to the following criteria: All ions present in the standard mass spe must be present in the sample spectrum. The relative intensities of these ions must sample spectra (e.g., for an ion with an a the corresponding sample ion abundance ions present at greater than 10% in the si	aboratory-generated standard [i.e., the mass ning CCV or mid-point standard from initial ctrum at a relative intensity greater than 10% agree within ±20% between the standard and abundance of 50% in the standard spectrum, must be between 30-70%). ample mass spectrum, but not present in the by a reviewer experienced in mass spectral
List compound	s not meeting the criteria described above:	
Sample ID	Compounds	Actions

_ldentified_compounds_meet_the_required_criteria____

Action:

- 1. The application of qualitative criteria for GC/MS analysis of target compounds requires professional judgment. It is up to the reviewer's discretion to obtain additional information from the laboratory. If it is determined that incorrect identifications were made, qualify all such data as unusable (R).
- 2. Use professional judgment to qualify the data if it is determined that cross-contamination has occurred.
- Note in the Data Review Narrative any changes made to the reported compounds or concerns regarding target compound identifications. Note, for Contract Laboratory COR action, the necessity for numerous or significant changes.

TENTATIVELY IDENTIFIED COMPOUNDS (TICS)

NOTE: Tentatively identified compounds should only be evaluated when requested by a party from outside of the Hazardous Waste Support Section (HWSS).

9 4	-	_
100		/ 'c
151		1.0

Sample ID	Compound	Sample ID	Compound

Action:

- 1. Qualify all TIC results for which there is presumptive evidence of a match (e.g. greater than or equal to 85% match) as tentatively identified (NJ), with approximated concentrations. TICs labeled "unknown" are qualified as estimated (J).
- 2. General actions related to the review of TIC results are as follows:
 - a. If it is determined that a tentative identification of a non-target compound is unacceptable, change the tentative identification to "unknown" or another appropriate identification, and qualify the result as estimated (J).
 - b. If all contractually-required peaks were not library searched and quantitated, the Region's designated representative may request these data from the laboratory.
- 3. In deciding whether a library search result for a TIC represents a reasonable identification, use professional judgment. If there is more than one possible match, report the result as "either compound X or compound Y". If there is a lack of isomer specificity, change the TIC result to a nonspecific isomer result (e.g., 1,3,5-trimethyl benzene to trimethyl benzene isomer) or to a compound class (e.g., 2-methyl, 3-ethyl benzene to a substituted aromatic compound).
- 4. The reviewer may elect to report all similar compounds as a total (e.g., all alkanes may be summarized and reported as total hydrocarbons).

- 5. Target compounds from other fractions and suspected laboratory contaminants should be marked as "non-reportable".
- 6. Other Case factors may influence TIC judgments. If a sample TIC match is poor, but other samples have a TIC with a valid library match, similar RRT, and the same ions, infer identification information from the other sample TIC results.
- 7. Note in the Data Review Narrative any changes made to the reported data or any concerns regarding TIC identifications.
- 8. Note, for Contract Laboratory COR action, failure to properly evaluate and report TICs

All criteria were met _X
Criteria were not met
and/or see below

SAMPLE QUANTITATION AND REPORTED CONTRACT REQUIRED QUANTITATION LIMITS (CRQLS)

Action:

- 1. When a sample is analyzed at more than one dilution, the lower CRQL are used unless a QC exceedance dictates the use of higher CRQLs from the diluted sample. Samples reported with an "E" qualifier should be reported from the diluted sample.
- 2. If any discrepancies are found, the Region's designated representative may contact the laboratory to obtain additional information that could resolve any differences. If a discrepancy remains unresolved, the reviewer must use professional judgment to decide which value is the most accurate. Under these circumstances, the reviewer may determine that qualification of data is warranted. Note in the Data Review Narrative a description of the reasons for data qualification and the qualification that is applied to the data.
- 3. For non-aqueous samples, if the solids is less than 10.0%, use professional judgment for both detects and non-detects. If the percent solid for a soil sample is greater than or equal to 10.0% and less than 30.0%, use professional judgment to qualify detects and non-detects. If the percent solid for a soil sample is greater than or equal to 30.0%, detects and non-detects should not be qualified (see Table 11).
- 4. Note, for Contract Laboratory COR action, numerous or significant failures to accurately quantify the target compounds or to properly evaluate and adjust CRQLs.
- 5. Results between MDL and CRQL should be qualified as estimated "J".
- 6. Results < MDL should be reported at the CRQL and qualified "U". MDLs themselves should not be reported.

Table 11. Percent Solids Actions for Semivolatile Analysis for Non-Aqueous Samples

Criteria	Action			
Citteria	Detects	Non-detects		
%Solids < 10.0%	Use professional judgment	Use professional judgment		
10.0% ≤ %Solids ≤ 30.0%	Use professional judgment	Use professional judgment		
%Solids > 30.0%	No qualification	No qualification		

SAMPLE QUANTITATION

The sample quantitation evaluation is to verify laboratory quantitation results. In the space below, please show a minimum of one sample calculation:

QUANTITATION LIMITS

A. Dilution performed

SAMPLE ID	DILUTION FACTOR	REASON FOR DILUTION
JC24978-4	40 X	1,4-Dioxane outside calibration range (scan mode)
JC24978-5	20 X	1,4-Dioxane outside calibration range (scan mode)
		and the second s
	1000	
	SST IN	
- SP		

		Critena were no	metX of met
FIELD DUPLICATE PA	RECISION		
Sample IDs:	JC24978-2/JC24978-3	Matrix:	Groundwater

Field duplicates samples may be taken and analyzed as an indication of overall precision. These analyses measure both field and lab precision; therefore, the results may have more variability than laboratory duplicates which only laboratory performance. It is also expected that soil duplicate results will have a greater variance than water matrices due to difficulties associated with collecting identical field duplicate samples.

The project QAPP should be reviewed for project-specific information.

Suggested criteria: if large RPD (> 50 %) is observed, confirm identification of the samples and note differences. If both samples and duplicate are <5 SQL, the RPD criteria is doubled.

COMPOUND	SQL ug/L	SAMPLE CONC.	DUPLICATE CONC.	RPD	ACTION
Field duplicate ar criteria < 50 % for			a package. RPD within	n the require	d guidance document

Action:

			All criteria were metX Criteria were not met and/or see below	
OTHER	RISSUES			
A.	System Perfor	mance		
List sa	mples qualified I	pased on the degradation of system	performance during simple analysis:	
Sample	e ID	Comments	Actions	
Action:				
during	sample analys	nent to qualify the data if it is determes. Inform the Contract Laboratory performance which significantly affer	nined that system performance has degraded y Program COR any action as a result of cted the data.	
B.	Overall Assess	verall Assessment of Data		
List sar	mples qualified t	pased on other issues:		
Sample		Comments	Actions	
 _No_ot	ther_issues_that		_dataResults_are_valid_and_can_be_used n_below	
Note:				

- 1. Use professional judgment to determine if there is any need to qualify data which were not qualified based on the Quality Control (QC) criteria previously discussed.
- 2. Write a brief narrative to give the user an indication of the analytical limitations of the data. Inform the Contract Laboratory COR the action, any inconsistency of the data with the Sample Delivery Group (SDG) Narrative. If sufficient information on the intended use and required quality of the data is available, the reviewer should include their assessment of the usability of the data within the given context. This may be used as part of a formal Data Quality Assessment (DQA).

- 3. Sometimes, due to dilutions, re-analysis or SIM/Scan runs are being performed, there will be multiple results for a single analyte from a single sample. The following criteria and professional judgment are used to determine which result should be reported:
 - The analysis with the lower CRQL
 - The analysis with the better QC results
 - The analysis with the higher results